

Tanaka TED-270PFHS Gas Powered High Speed Coring Drill

SPECIFICATIONS

ENGINE

Engine Type:	Two-Stroke
Displacement CC (CU. IN.):	27
Output H.P.:	1.4
Fuel Tank Capacity FL. OZ. (CC):	22.7 (670)
Cylinder:	Chrome Plated, Stress Relieved
Connecting Rod:	Forged Steel
Carburetion:	Walbro® Diaphragm w/ Primer
Starting System:	Standard Recoil
Ignition System:	Transistorized Electronic
Clutch System:	Heavy-duty Centrifugal

DRILL RELATED

Reduction Ratio:	8:1
Chuck Capacity - In. (mm):	1/2 (12.7)
Max Bit Size - In. (mm):	1 (25) Wood, 1/2 Steel, 1/2 Concrete
Adapter Size - In. (mm):	1 (25)

MISC.

Dry Weight / LBS. (KG):	10.8 (4.9)
Shipping Weight / LBS. (KG):	17 (7.2) (One carton)
EPA Phase 2 Compliant:	Yes
C.A.R.B. Tier II Compliant:	Yes
Gas / Oil Ratio:	50:1
Warranty:	Two-year commercial use warranty / Seven-year consumer use warranty / One-year rental use warranty
Packaging:	One carton