

INTRODUCING THE

THREE IN ONE ED3777

180 DEGREE COVERAGE, MULTIPLE FLASH PATTERNS AND VARIOUS MOUNTING OPTIONS PROVIDE SUPERIOR WARNING CAPABILITY



Locators & Supplies, Inc
800-950-6666
sales@locatorsandsupplies.com
www.locatorsandsupplies.com

COBERTURA DE 180 GRADOS TRES EN UNO, MÚLTIPLES PATRONES DE PARPADEO Y DIVERSAS OPCIONES DE ENSAMBLAJE QUE OFRECEN UNA CAPACIDAD DE ADVERTENCIA SUPERIOR.
COUVERTURE DE 180 DEGRÉS TROIS EN UN, PLUSIEURS MODES DE CLIGNOTEMENT ET DIVERSES OPTIONS DE MONTAGE OFFRENT UNE CAPACITÉ D'AVERTISSEMENT SUPÉRIEURE.



directional LED

LED direccional | LEDs directionnels

ED3777 **NEW**

SAE Class I

Single- or Dual-Color Multi-Mount



- # **ED3777A** \$112.00
- C Amber
- V 12-24
- A 1.8
- X Multi-Mount (surface, tilt bracket, self-adhesive, edge)
- ✓ SAE J595 Class I, R10
- ⌚ 3 Year



- # **ED3777AW** \$132.00
- C Amber/White
- V 12-24
- A 3.6
- X Multi-Mount (surface, tilt bracket, self-adhesive, edge)
- ✓ SAE J595 Class I, Cal. Title 13, R65, CE, R10, IP67
- ⌚ 3 Year

DIMENSIONS DIMENSIONES | DIMENSIONS
1.3 [29] H x 5.1 [130] W x .875 [21] D

AVAILABLE COLORS COLORES DISPONIBLES | COULEURS DISPONIBLES
Amber, Blue, Green, Red & White



Locators & Supplies, Inc
800-950-6666
sales@locatorsandsupplies.com
www.locatorsandsupplies.com

Dual-Color

Single-Color



Tilt bracket / self-adhesive



Edge Mount

180 degree warning lights, with worklight and puddle light combinations
Luces de advertencia de 180 grados con combinaciones de luz de trabajo y luz de charcos
Éclairage d'avertissement de 180 degrés, combinaisons de lumières de travail et d'entrée de porte

Six LEDs per color
Seis LED por color
Six LED par couleur

Single- or dual-color options
Opciones de color soltero o doble
Options de couleurs unique ou double

13 flash patterns
13 patrones de parpadeo
13 modes de clignotement

Synchronization capable
Capacidad de sincronización
Capacité de synchronisation

4 mounting options (hardware included)
4 opciones de ensamblaje (accesorios incluidos)
4 options de montage (matériel inclus)